



Technical Specs:

- Insulator: Black glass filled polyester PPS-GF30-FR
- Flammability: UL 94V-O
- Sleeve: Brass CuZn36Pb3 (C36000)
- Contact clip (6 finger): Beryllium copper (C17200)
- Mating pins: Outside Diameter 0.70 to 0.90 mm
- Forces: (polished steel gauge 0.64 mm)
- Insertion: 2 N typ.
- Withdrawal: 1 N typ.
- Mechanical life: min 500 cycles
- Rated current: 3 A
- Contact resistance: max 20 Milliohms
- Dielectric strength: min 1000 V RMS

E		Units	mm	Scale	2:1	Drawing By	Date	C N T 肯耐特电子有限公司					
D		Tolerance Unless				Reviewed By	Date				Date	2004/07/12	Title
C		Otherwise Specified									Sheet	1 of 1	2.54mm SIP Socket H=7.00mm Straight DIP Type
B				.X ~	± 0.30	Approval By	Date	Thirt Angle Projection		Drawing No.			
A				.XX ~	± 0.25					F/Name			
REV				.XXX ~	± 0.20					CNT-IC254-1XXX-HS-700/3.0			
				Angle ~	$\pm 3^\circ$					REV			
										A			

REV		ECN. NO.	Date
A		RELEASED	07/12/04
B			
C			
D			
E			